






-  Walk behind machine
with or without traction
-  Battery autonomy
2 - 4 h
-  Operating tension
24 V / 110 Ah
-  Cleaning width
450 mm
-  Solution tank / recovery tank
40 / 45 l
-  Disc brushes
2 x 235 mm
-  Brushes pressure adjustable
max. 22,5 kg
-  Brushes speed
350 rpm



Theoretical working capacity

1575 / 1800 m²/h

Technical data

Squeegee width	750 mm
Brushes motor	420 Watt
Type of drive	semi-automatic/automatic
Maximum gradient	2 %
Suction motor	570 Watt
Suction vacuum	120 mbar
Machine dimensions	
length	1102 mm
height	1053 mm
width without squeegee	527 mm
Machine weight without battery	71 / 81 kg
Traction motor	-- / 120 Watt
Movement speed	-- / 4 km/h
Battery compartment	
length	342 mm
width	345 mm
height	300 mm
Class	III
Protection level	IP 23
Noise level	67,3 / 67,6 dB (A)

Floor scrubbing machine, battery-driven, with brushes base group of 45 cm.


The two models differ from the presence or not of the traction system.

The brushes pressure is adjustable from the operator in function of the floor to be cleaned.


In the semi-automatic version the brushes inclination can be adjusted for easy driving.

Thanks to the solid structure, the easiness of maintenance and the simplicity of the controls, working with the ruby becomes simple obtaining an elevated cleaning quality.







Walk behind machine
with or without traction



Battery autonomy
2 - 4 h




Operating tension
24 V / 110 Ah



Cleaning width
550 mm




Solution tank / recovery tank
40 / 45 l



Disc brushes
2 x 285 mm



Brushes pressure adjustable
max. 24,5 kg



Brushes speed
280 rpm



Theoretical working capacity

1925 / 2200 m²/h

Technical data

Squeegee width	750 mm
Brushes motor	420 Watt
Type of drive	semi-automatic/automatic
Maximum gradient	2 %
Suction motor	570 Watt
Suction vacuum	120 mbar
Machine dimensions	
length	1140 mm
height	1053 mm
width without squeegee	586 mm
Machine weight without battery	74 / 84 kg
Traction motor	-- / 120 Watt
Movement speed	-- / 4 km/h
Battery compartment	
length	342 mm
width	345 mm
height	300 mm
Class	III
Protection level	IP 23
Noise level	66,2 / 67,6 dB (A)

Floor scrubbing machine, battery-driven, with a brushes head of 55 cm having two counter-rotating brushes.

The two models differ from the presence or not of the traction system.

The brushes pressure is adjustable from the operator in function of the floor to be cleaned.

In the semi-automatic version the brushes inclination can be adjusted for easy driving.

Suitable for any type of environment.

The traction version is equipped with a reliable geared motor making the machine very agile in its use, also in narrow areas. It is therefore recommended for faster cleaning.

